

IMPACT 5000 Series

IMPACT SDW 5016 / 5015
IMPACT SDW 5013

Meet the future prepared

IMPACT SDW 5016 is a wireless DECT headset system for modern office professionals, providing future-proof device flexibility, next generation communication quality and advanced security to modern work environments. IMPACT SDW 5016 meets the challenges of evolving modern workplaces by providing a communication tool that lives up to users' expectations for multi-device usability, security and seamless customer interaction.

Modern office workers require mobility in the office and the ability to hold ad hoc collaborative meetings. Using multiple devices and often sitting at different desks, today's knowledge workers demand a flexible, personal communication solution that simply works. IMPACT SDW 5016 helps them meet the future prepared with the ultimate business communication tool.

- Superior sound:
Natural, rich sound with super wideband audio
- Total flexibility:
A hub for all your people, audio sources and headsets
- Higher productivity:
Busy light and advanced collaboration features
- Enhanced security:
With protected pairing and DECT Security certification

See more at eposaudio.com/impact-sdw5000



Key benefits & features

Crisp and natural sound with super wideband, for voice clarity that exceeds conventional business standards

Exceptional speech intelligibility with two microphone noise-cancelling system and pioneering own-voice detection technology

Sound clarity in high density environments with high density wideband mode

Hearing protection from acoustic shock by ensuring that the sound pressure level does not exceed 118 dB

Optimized for major UC brands and certified for Skype for Business

Manage all calls from one headset with triple connectivity to computer, desk and mobile phone*

* Connectivity depending on product variant



IMPACT 5000 Series

Superior sound

Successful communication is the key to an efficient business. The IMPACT SDW 5000 Series sets a new sound standard and features super wideband sound offering a voice experience beyond conventional business standards. Hear conversational nuances and experience a natural and richer sound for both communication and multimedia. Two microphone noise-cancelling system and pioneering own-voice detection technology deliver exceptional sound for improved speech intelligibility in noisy environments. A new wideband mode for communication in high density environments provides excellent sound for more users.

Total flexibility



Answer all calls from a single device. With up to triple connectivity for softphone/PC, desk phone and mobile devices, the IMPACT SDW 5016 allows users to choose their own combination using the base station as a gateway to their preferred audio sources. It is also possible to connect a wired EPOS headset/speakerphone or a Bluetooth® headset (via the BTD 800 USB dongle) using the USB port on the base station. IMPACT SDW 5016 offers a choice of three wearing styles to cover all wearing preferences – a headband, ear hook and neckband solution for the perfect customized fit.*

Higher productivity

IMPACT SDW 5000 Series offers an array of smart features to enable seamless communication and collaboration for improved productivity. The busy light on the headset helps users to remain undisturbed during calls and conferences, and smart headset and base station controls deliver easy call management. The cloud-based EPOS Manager puts IT managers in control of all EPOS devices and manages assets, updates and configurations from one location. The IMPACT SDW 5016 is UC optimized and certified for Skype for Business to maximize productivity.

Enhanced security

Security is a primary concern for a company's IT manager. IMPACT SDW 5016 comes with advanced security protocols to ensure that all communication is kept confidential. The IMPACT 5000 Series is DECT Security certified* and designed with special focus on secure pairing, the most vulnerable part of a wireless system. The authentication process uses 128-bit keys and Protected Pairing ensures that sensitive pairing data cannot be intercepted over-the-air. EPOS Manager allows the IT manager to disable Bluetooth®, call merging and conferencing mode if required.



* DECT SECURITY is the trademark of DECT Forum. The trademark may only be applied to products with the written licence of DECT Forum.

IMPACT 5000 Series

Product data

General

| | |
|---------------------|---|
| Product description | <p>IMPACT SDW 5016: Wireless DECT headset with base station. Triple connectivity to desk phone, PC/softphone and mobile devices. UC optimized and Certified for Skype for Business.</p> <p>IMPACT SDW 5015: Wireless DECT headset with base station. Dual connectivity to desk phone and PC/softphone. UC optimized and Certified for Skype for Business.</p> <p>IMPACT SDW 5013: Wireless DECT headset with base station. Single connectivity to softphone/PC. UC optimized and Certified for Skype for Business.</p> |
| Wearing style | Single-sided headset with three wearing styles – headband, ear hook and neckband |
| Weight | 44 g / 1.55 oz. (Ear hook version) 58 g / 2.05 oz. (Headband version) 43 g / 1.52 oz. (Neckband version) |
| Ear pad size | ø 53 mm / 2.09 in |
| Personalization | Yes with nameplate on headset |
| Warranty | 2 years |

Audio

| | |
|----------------------------|---|
| Microphone | Digital MEMs microphones – two microphone noise-cancelling system for exceptional speech clarity |
| Microphone frequency range | 100 Hz – 11.0 kHz (Super wideband) 100 Hz – 7.5 kHz (Wideband) 150 Hz – 3.5 kHz (Narrowband) |
| Speaker type | High-quality Neodymium Magnet Speaker for outstanding audio quality |
| Speaker frequency range | 100 Hz – 11.0 kHz (Super wideband) 100 Hz – 7.5 kHz (Standard wideband and High density wideband) 150 Hz – 3.5 kHz (Narrowband) |

Technical

| | |
|---------------------------|--|
| DECT | 1.880 to 1.900 MHz (EU, UK, AUS) 1.920 to 1.930 MHz (US) |
| GAP compatible | Yes (Headset) |
| Headset | Connects to base station |
| Base station | SDW 5 BS connects to desk phone, softphone and up to two mobile devices simultaneously (Included in SDW 5016 and SDW 5015) SDW 3 BS connects to softphone/PC and up to two mobile devices devices simultaneously (Included in SDW 5013) |
| BTD 800 USB dongle | For more information please see eposaudio.com/btd-800-usb (Included in SDW 5016) |
| USB-A port | Supports call handling with EPOS devices and smartphone charging |
| Temperature range | Operational: +5 °C to + 45 °C / +41 °F to +113 °F Storage: -20 °C to + 70 °C / -4 °F to +158 °F |
| Battery (lithium polymer) | Exchangeable by service |

IMPACT 5000 Series

Product data

Technical

| | |
|-----------------------------------|---|
| Range | Line of sight: 180 m / 590 ft Typical office building: 55 m / 180 ft |
| Automatic power adjustment | Yes (distance between headset and base) |
| Talk time | Up to 10 hours (Narrowband) Up to 7 hours (Density optimized wideband) Up to 8 hours (Wideband) Up to 6 hours (Super wideband) |
| Standby time | Up to 48 hours |
| Auto sleep mode when out of range | Yes, after 12 hours |
| Charge time | 0-50%: 30 minutes 0-100%: 1 hour |

Hearing protection

| | |
|---|--|
| EPOS ActiveGard® technology | Protect users against acoustic injury caused by sudden sound burst on the line |
| EU*/AUS Limiter depending on regional variant | Activation by dip switch, EPOS Connect and EPOS Manager software |

Security

| | |
|------------------------------|-------------------------|
| Pairing intrusion protection | Protected pairing |
| Certification | DECT Security certified |

Content of delivery

| | |
|-------------------|---|
| What's in the box | <p>SDW 5016/SDW 5015 SDW 5 BS Base station, headset, headband, wearing style adapter with pre-mounted earhook, earbud (M) and cheek spacer, ear hook stabilizer, neckband, extra earbuds (S, L), BTD 800 USB dongle (Included in SDW 5016), USB cable, power supply, audio phone cable, printed quick guides (headset and base station), printed safety guide, printed compliance sheet</p> <p>SDW 5013 SDW 3 BS Base station, headset, headband, wearing style adapter with pre-mounted earhook, earbud (M) and cheek spacer, ear hook stabilizer, neckband, extra earbuds (S, L), BTD 800 USB dongle, USB cable, power supply, audio phone cable, printed quick guides (headset and base station), printed safety guide, printed compliance sheet</p> |
|-------------------|---|

Software

EPOS devices can be managed with following Software solutions:

| | |
|--------------|--|
| EPOS Connect | Conduct firmware updates and configure headsets for personal audio preferences. EPOS Connect works for Windows, Mac and VDI/Thin client environments: eposaudio.com/software-epos-connect |
| EPOS Manager | Manage, update and configure EPOS audio devices from any location - For both cloud and on-premises solutions: eposaudio.com/software-epos-manager |

Software compatibility

| | |
|--------------------|---|
| UC & CC Compatible | Use our Compatibility tool to find the choices available to you and to learn about the different headset features: eposaudio.com/compatibility |
|--------------------|---|

*Noise At Work: The EU's „Noise At Work Directive“ (2003/10/EC) sets limits for two types of noise in the workplace: Acoustic burst and Sustained Noise.

IMPACT 5000 Series

Additional benefits & features

Maximum flexibility via one single base station

– works with all IMPACT 5000 headsets and connects to a EPOS Bluetooth® headset or a wired headset or speakerphone

Perfect customized fit

with the FlexFit™ system, offering 3 wearing style solutions. Choose between headband, ear hook or neckband

Undisturbed calls

with a busy light on the headset. A busy light for the desk is available as an accessory.

Easy configuration and management

for IT managers with EPOS Manager

Enhanced security

with protected pairing, 128-bit authentication and DECT Security certification to keep all conversations confidential

Long distance wireless range

– up to 180 m/ 590 ft with line of sight

Hot desking

with fast, secure headset pairing

Easy to set up phone conferences

of up to 4 IMPACT SDW 5000 headsets with the same base station

Full workday of talk time

– up to 10 hours narrowband

Fast charging

with 50 % battery in just 30 minutes

Product overview

| Connects to | Product | Details | EAN / UPC code |
|---|---|---|---|
| Desk phone, PC/softphone, Mobile devices  | SDW 5016 - EU/UK/AUS Art. no. 1001024 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00826 2 UPC: 8 40064 40826 4 |
| | SDW 5016 - US Art. no. 1000621 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00422 6 UPC: 8 40064 40422 8 |
| | SDW 5015 - EU/UK/AUS Art. no. 1001021 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00823 1 UPC: 8 40064 40823 3 |
| Desk phone, PC/softphone  | SDW 5015 - US Art. no. 1000597 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00398 4 UPC: 8 40064 40398 6 |
| | SDW 5015 - JP Art. no. 1000647 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00448 6 UPC: 8 40064 40448 8 |
| | SDW 5013 - EU/UK/AUS Art. no. 1001015 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00817 0 UPC: 8 40064 40817 2 |
| PC/softphone  | SDW 5013 - US Art. no. 1000585 | Optimized for UC and Certified for Skype for Business | EAN: 57 14708 00386 1 UPC: 8 40064 40386 3 |

IMPACT 5000 Series

Spare Parts & Accessories

| Product | Art. no. | Description | EAN / UPC code |
|------------------------------|----------|---|---|
| SDW D1 Accessory Pack | 1000982 | Carry pouch and USB-A charging cable for IMPACT 5000 headsets | EAN: 57 14708 00784 5 UPC: 8 40064 40784 7 |
| SDW D1 USB | 1000299 | USB DECT dongle | EAN: 57 14708 00100 3 UPC: 8 40064 40100 5 |
| SDW D1 USB - US | 1000978 | USB DECT dongle | EAN: 57 14708 00780 7 UPC: 8 40064 40780 9 |
| SDW 10 HS | 1000631 | Headset for SDW 5016, SDW 5015 and SDW 5013 with three wearing styles | EAN: 57 14708 00432 5 UPC: 8 40064 40432 7 |
| SDW 5 BS - EU/UK/AUS | 1001027 | Base station for SDW 5016 and SDW 5015 (without BTD 800 dongle) | EAN: 57 14708 00829 3 UPC: 8 40064 40480 8 |
| SDW 5 BS - US | 1000681 | Base station for SDW 5016 and SDW 5015 (without BTD 800 dongle) | EAN: 57 14708 00482 0 UPC: 8 40064 40482 2 |
| SDW 3 BS - EU/UK/AUS | 1001028 | Base station for SDW 5013 (without BTD 800 dongle) | EAN: 57 14708 00830 9 UPC: 8 40064 40830 1 |
| SDW 3 BS - US | 1000685 | Base station for SDW 5013 (without BTD 800 dongle) | EAN: 57 14708 00486 8 UPC: 8 40064 40486 0 |

